


FR Series



Type	Wheel Type	Dimensions (mm)																	Load(KN)		
		A	B	C	D	e	F	G	H	L	D1	D2	D3	D4	D5	d	d1	DP	R	Cw	Cow
V	FR10	22.62	10.5	10	1	1	2	7	15.4	30	6.4	15	20.8	11	42	9	2.6	3	200	4.9	5.3
-	FR10Z	22.62	10.5	10	1	0	2	7	15.4	30	6.4	15	20.8	11	42	9	2.6	3	200	4.9	5.3
Rail	FR15	29.65	12	12	1	1	2	9	18.5	35	8.4	15	23.8	14	53	14	2.6	3	250	7.2	6.8
-	FR15Z	29.65	12	12	1	0	2	9	18.5	35	8.4	15	23.8	14	53	14	2.6	3	250	7.2	6.8
-	FR20	36.2	16	15	1	1	3	11	22.5	46	10.5	20	22.7	18	63	20	2.6	3	300	10.2	9.5
-	FR20Z	36.2	16	15	1	0	3	11	22.5	46	10.5	20	22.7	18	63	20	2.6	3	300	10.2	9.5
Guide	FR22	39.4	16	15	1	2	3	11	27.5	46	10.5	20	33	18	70	20	2.6	3	300	24.6	16.2
-	FR22Z	39.4	16	15	1	0	3	11	27.5	46	10.5	20	33	18	70	20	2.6	3	300	24.6	16.2
Wheel	FR25	43.42	20.5	20	1	1	3.5	13	27.5	60	13	25	35.6	20	77	24	4.1	4.5	360	16.3	15
-	FR25Z	43.42	20.5	20	1	0	3.5	13	27.5	60	13	25	35.6	20	77	24	4.1	4.5	360	16.3	15
-	FR35	61.25	30	25	1	1	7.5	18	42	84	17	40	56.9	30		35	4.1	4.5	500	28.4	32
-	FR35Z	61.25	30	25	1	0	7.5	18	42	84	17	40	56.9	30		35	4.1	4.5	500	28.4	32
-	LR10	-	10.5	10	1	1	2	7	15.4	30	6.4	15	20.8	11	47	-	2.6	3	500	4.9	5.3
-	LR10Z	-	10.5	10	1	0	2	7	15.4	30	6.4	15	20.8	11	47	-	2.6	3	500	4.9	5.3
Wheel	LR15	-	12	12	1	1	2	9	18.5	35	8.4	15	23.8	14	47	-	2.6	3	500	7.2	6.8
-	LR15Z	-	12	12	1	0	2	9	18.5	35	8.4	15	23.8	14	47	-	2.6	3	500	7.2	6.8
-	LR20	-	16	15	1	1	3	11	22.5	46	10.5	20	22.7	18	72	-	2.6	3	500	10.2	9.5
-	LR20Z	-	16	15	1	0	3	11	22.5	46	10.5	20	22.7	18	72	-	2.6	3	500	10.2	9.5
-	LR25	-	20.5	20	1	1	3.5	13	27.5	60	13	25	35.6	20	85	-	4.1	4.5	500	16.3	15
-	LR25Z	-	20.5	20	1	0	3.5	13	27.5	60	13	25	35.6	20	85	-	4.1	4.5	500	16.3	15
-	LR35	-	30	25	1	1	7.5	18	42	84	17	40	56.9	30		-	4.1	4.5	500	28.4	32
-	LR35Z	-	30	25	1	0	7.5	18	42	84	17	40	56.9	30		-	4.1	4.5	500	28.4	32