



NUTR Series



NUTR



NUTR...X

Bearing Designation Without Seal	Outer Diameter [mm]	Boundary Dimensions [mm]							Basic Load Ratings(N)						Limiting Speed
		d	D	B	C	d1	rs min	ris(min)	C	Co	Cw	Cow	Fr perm	For perm	
NUTR 15	35	15	35	19	18	20	0.6	0.3	23000	27000	16000	18300	8300	16400	6500
NUTR 17	40	17	40	21	20	22	1	0.3	24800	31000	18500	22800	13200	22800	5500
NUTR 15 42	42	15	42	19	18	20	0.6	0.3	23000	27000	19400	23800	23900	23900	6500
NUTR 17 47	47	17	47	21	20	22	1	0.3	24800	31000	21300	28000	28000	28000	5500
NUTR 20	47	20	47	25	24	27	1	0.3	39000	50000	28000	35000	16500	33000	4200
NUTR 20 52	52	20	52	25	24	27	1	0.3	39000	50000	31500	41000	38500	41000	4200
NUTR 25	52	25	52	25	24	31	1	0.3	43500	60000	29000	37500	17300	34500	3400
NUTR 25 62	62	25	62	25	24	31	1	0.3	43500	60000	35500	50000	50000	50000	3400
NUTR 30	62	30	62	29	28	38	1	0.3	59000	79000	40000	51000	23600	47000	2600
NUTR 30 72	72	30	72	29	28	38	1	0.3	59000	79000	48000	65000	65000	65000	2600
NUTR 35	72	35	72	29	28	44	1.1	0.6	65000	93000	45000	61000	32000	61000	2100
NUTR 35 80	80	35	80	29	28	44	1.1	0.6	65000	93000	51000	72000	72000	72000	2100
NUTR 40	80	40	80	32	30	51	1.1	0.6	90000	134000	56000	76000	30500	60000	1600
NUTR 45	85	45	85	32	30	55	1.1	0.6	95000	147000	56000	79000	31500	61000	1400
NUTR 40 90	90	40	90	32	30	51	1.1	0.6	90000	134000	66000	96000	84000	96000	1600
NUTR 50	90	50	90	32	30	60	1.1	0.6	100000	161000	57000	81000	32000	63000	1300
NUTR 45 100	100	45	100	32	30	55	1.1	0.6	95000	147000	72000	10800	106000	108000	1400
NUTR 50 110	110	50	110	32	30	60	1.1	0.6	100000	161000	76000	121000	121000	121000	1300