


Single-row Four Point Contact Ball Type Slewing Bearing (Non-gear type)



Designations	Boundary Dimension [mm]			Bolt Hole Diameter [mm]						Basic load ratings(KN)	Weight [Kg]
	Da	Di	H	D1	D2	n1	n2	φ1	φ2		
010.30.500	602	398	80	566	434	20	20	18	18	1290	75.8
010.30.560	662	458	80	626	494	20	20	18	18	1440	94
010.30.630	732	528	80	696	564	24	24	18	18	1870	110
010.30.710	812	608	80	776	644	24	24	18	18	2120	120
010.30.955.11	1098	893	90	1060	845	48/47		22	22	2700	126
010.40.800	922	678	100	878	722	30	30	22	22	3130	256
010.40.900	1022	778	100	978	822	30	30	22	22	3550	240
010.40.100	1122	878	100	1078	922	36	36	22	22	3940	305
010.40.1120	1242	998	100	1198	1042	36	36	22	22	4430	300
010.45.1250	1390	1110	110	1337	1163	40	40	26	26	5540	420
010.45.1400	1540	1260	110	1487	1313	40	40	26	26	6170	480
010.45.1600	1740	1460	110	1687	1513	45	45	26	26	7020	550
010.40.1800	1940	1660	110	1887	1713	45	45	26	26	7930	610
010.60.2000	2178	1825	144	2110	1891	48	48	33	33	12100	1100
010.60.2240	2418	2065	144	2350	2131	48	48	33	33	13500	1250
010.60.2500	2678	2325	144	2610	2391	56	56	33	33	15000	1400
010.60.2800	2978	2625	144	2910	2691	56	56	33	33	16800	1600
010.75.3150	3376	2922	174	3286	3014	56	56	45	45	23800	2800
010.75.3550	3776	3322	174	3686	3414	56	56	45	45	26900	3200
010.75.4000	4226	3772	174	4136	3864	60	60	45	45	30200	3600
010.75.4500	4726	4272	174	4636	4364	60	60	45	45	34100	4000
116752	480	260	60	444	296	16	16	14	14	750.4	55
176792	590	460	45	570	488	8	12	10	10	620.6	35.9

Single-row Four Point Contact Ball Type Slewing Bearing (Non-gear

176792K2M	590	460	45	570	488	12	8	10	10	940.4	30.8
1167/530	780	530	60	740	560	20	20	17	13	1120	103
1167/560K	720	560	36	690	590	12	32	12	16	700.8	39.2
E787/760G2	950	760	80	915	795	24	24	18	16	203	138
787/800	1050	800	90	1012	838	30	30	20	20	2150	192
71769/850Y	1120	850	85	1074	924	12	12	20	22	1510	248
787/932G2	1200	932	120	1148	984	40	40	26	24	3490	328