



Bearing No.	Boundary dimensions [mm]			Basic load ratings (kN)		Limiting speed (rpm) Oil	Mass Kg
	Fw	D	C	Dynamic (Cr)	Static (Cor)		
HK0812-2RS	8	12	12	2250	2100	19000	3.5
HK1014-2RS	10	14	14	4100	5000	15000	5.2
HK1216-2RS	12	18	16	6100	7000	12000	11.5
HK1416-2RS	14	20	16	6100	7500	11000	14
HK1516-2RS	15	21	16	6800	8800	10000	14.3
HK1520-2RS	15	21	20	9500	11400	10000	18
HK1616-2RS	16	22	16	7200	9200	10000	15.1
HK1620-2RS	16	22	20	9900	12300	10000	16.8
HK1625-2RS	16	22	25	9900	12300	10000	17
HK1816-2RS	18	24	16	7800	9900	9200	17
HK2016-2RS	20	26	16	8000	10100	9000	18.8
HK2020-2RS	20	26	20	12700	20100	7800	23.5
HK2216-2RS	22	28	16	9000	12400	7800	20.3
HK2220-2RS	22	28	20	10400	20100	7800	25.5
HK2516-2RS	25	32	16	9800	13200	6900	27.3
HK2520-2RS	25	32	20	13600	20000	6900	33.1
HK2524-2RS	25	32	24	17900	30000	6900	39.7
HK2530-2RS	25	32	30	24500	43000	6900	47.3
HK2820-2RS	28	35	20	11400	22500	5300	36.9
HK3016-2RS	30	37	16	10100	16200	5300	28.5
HK3020-2RS	30	37	20	16200	26000	5300	39.1

HK...2RS Series

HK3024-2RS	30	37	24	21000	38500	5300	49.7
HK3516-2RS	35	42	16	10100	20300	4900	36.4
HK3520-2RS	35	42	20	16700	30500	4900	41.1
HK4016-2RS	40	47	16	11000	21300	4200	41.2
HK4020-2RS	40	47	20	19000	30500	4200	50.2
HK4520-2RS	45	52	20	20300	41000	3800	57.4
HK5024-2RS	50	58	24	30000	61000	3200	84