

S6200 Series

Bearing NO.	Shape Dimension(mm)						Basic Load Rating(N)		Weight		
	d(mm)	d(inch)	D(mm)	D(inch)	B(mm)	B(inch)	r min(mm)	r min(inch)	Dynamic(Cr)	Static(Cor)	(kg)
S6200	10	0.3937	30	1.1811	9	0.3543	0.6	0.0236	5110	2380	0.0320
S6201	12	0.4724	32	1.2598	10	0.3937	0.6	0.0236	6180	3060	0.0370
S6202	15	0.5906	35	1.3780	11	0.4331	0.6	0.0236	7450	3700	0.0450
S6203	17	0.6693	40	1.5748	12	0.4724	0.6	0.0236	9560	4780	0.0650
S6204	20	0.7874	47	1.8504	14	0.5512	1	0.0394	12840	6650	0.1060
S6205	25	0.9843	52	2.0472	15	0.5906	1	0.0394	14020	7930	0.1280
S6206	30	1.1811	62	2.4409	16	0.6299	1	0.0394	19460	11310	0.1990
S6207	35	1.3780	72	2.8346	17	0.6693	1.1	0.0433	25670	15300	0.2880
S6208	40	1.5748	80	3.1496	18	0.7087	1.1	0.0433	29520	18140	0.3660
S6209	45	1.7717	85	3.3465	19	0.7480	1.1	0.0433	31500	20400	0.4200
S6210	50	1.9685	90	3.5433	20	0.7874	1.1	0.0433	35000	23200	0.4590