

S6000 Series

Bearing NO.	Shape Dimension(mm)						Basic Load Rating(N)		Weight		
	d(mm)	d(inch)	D(mm)	D(inch)	B(mm)	B(inch)	r min(mm)	r min(inch)	Dynamic(Cr)	Static(Cor)	(kg)
S6000	10	0.3937	26	1.0236	8	0.3150	0.3	0.0118	4160	1780	0.0190
S6001	12	0.4724	28	1.1024	8	0.3150	0.3	0.0118	5110	2380	0.0220
S6002	15	0.5906	32	1.2598	9	0.3543	0.3	0.0118	5590	2840	0.0300
S6003	17	0.6693	35	1.3780	10	0.3937	0.3	0.0118	6000	3250	0.0390
S6004	20	0.7874	42	1.6535	12	0.4724	0.6	0.0236	9390	5020	0.0690
S6005	25	0.9843	47	1.8504	12	0.4724	0.6	0.0236	10060	5860	0.0800
S6006	30	1.1811	55	2.1654	13	0.5118	1	0.0394	11900	7460	0.1160
S6007	35	1.3780	62	2.4409	14	0.5512	1	0.0394	16210	10420	0.1550
S6008	40	1.5748	68	2.6772	15	0.5906	1	0.0394	17030	11700	0.1920
S6009	45	1.7717	75	2.9528	16	0.6299	1	0.0394	21080	14780	0.2450
S6010	50	1.9685	80	3.1496	16	0.6299	1	0.0394	22000	16260	0.2610